

## 33020

**Valvola di ritegno 120 Bar con pastiglia di tenuta in ptfe e guarnizioni in neoprene + ptfe con attacco tubo in rame**

120 Bar check valve with ptfe seal, and neoprene + ptfe gaskets with copper pipe connection



Codice Code	Attacchi Connections		Ps [bar]	Kv [m³/h]	Pd [bar]	TS (°C)	
	∅ [In]	∅ [mm]				Min	Max
33020-TS-01-D	1/4		120	0,6	0,1	-35	105
33020-TS-02-D	3/8		120	1,5	0,1	-35	105
33020-TS-M06-D		6	120	0,6	0,1	-35	105
33020-TS-M10-D		10	120	1,5	0,1	-35	105

## 33020



**Valvola di ritegno 120 Bar con pastiglia di tenuta in ptfe e guarnizioni in HNBR + PTFE con attacco tubo in rame**

120 Bar check valve with ptfe seal, and HNBR + ptfe gaskets with copper pipe connection



Codice Code	Attacchi Connections		Ps [bar]	Kv [m³/h]	Pd [bar]	TS (°C)	
	∅ [In]	∅ [mm]				Min	Max
33020-TS-01-D	1/4		120	0,6	0,1	-40	150
33020-TS-02-D	3/8		120	1,5	0,1	-40	150
33020-TS-M06-D		6	120	0,6	0,1	-40	150
33020-TS-M10-D		10	120	1,5	0,1	-40	150